

Mitsubishi Pajero NM 2002 3.2l DiD

SERVICE SPECIFICATIONS FRONT SUSPENSION

Items		Standard value
Toe-in At the centre of tyre tread	mm	2.5 ± 2.5
	Toe-angle (per wheel)	0° 05' ± 05'
Toe-out angle on turns (inner wheel when outer wheel at 20°)		21°48'
Camber		0°30' ± 30.*
Caster		3°50' ± 1°*
Side slip mm (per 1 m)		0 ± 3
Kingpin inclination		11°30'
Upper arm ball joint rotation torque Nxm		0.4 -2.5
Lower arm ball joint rotation torque Nxm		0.3 -4.5
Stabilizer link ball joint turning torque Nxm		0.5 -2.0

NOTE

*: difference between right and left wheels: less than 30'

SERVICE SPECIFICATIONS REAR SUSPENSION

Items		Standard value
Toe-in At the centre of tyre tread mm		3 ± 3
	Toe-angle (per wheel)	1° 06' ± 1° 06'
Camber		0° ± 30.*
Thrust angle		0° ± 9'
Upper arm ball joint rotation torque Nxm		0.5 -3.0
Stabilizer link ball joint turning torque Nxm		0.5 -2.0
Toe control arm ball joint turning torque Nxm		1.0 -2.5

NOTE

*: difference between right and left wheels: less than 30'